

Medium Pressure

HOK 80/120 1CT

Medium Pressure Mercury lamps are available in a wide range with an arc length between 10 and 140 centimeter. The lamps can be fitted with various types of end fitting from our catalogue, or equipped with customer special fittings, cables or pins. The lamps are made from selected types of quartz glass, with transmission characteristics tailored to the application. Medium Pressure Mercury lamps contain sophisticated quantities of mercury bromides, providing a self-cleaning halogen cycle, to control the depreciation of UV radiation over lamp life.

Product data

• General Characteristics

Cap-Base SK32
Cap-Base Information Cable 250mm
Execution -

Operating Position p10

Main Application Industrial UV Run Time 0.083 (max) hr

• Electrical Characteristics

Lamp Wattage 6400 W Lamp Wattage Tech- 9600 W

nical

Lamp Voltage 960 (min), 1030 (nom), 1100 (max) V

Lamp Current 10.5 A
Ignition Time 10 (max) s
Re-ignition Time 10 (max) min
Consumed Watt per 120 W/cm

cm

• Product Dimensions

Overall Length C 880 (max) mm Diameter D 24 (max) mm Arc Length O 800 mm

• Luminaire Design Requirements

Pinch Temperature 300 (max) C Bulb Temperature 600 (min), 900 (max) C

• Product Data

Order code 928189305104
Full product code Full product name Order product name Pieces per pack 928189305104
HOK 80/120 1CT/4

Pieces per pack 1
Packing configuration 4
Packs per outerbox 4

Bar code on pack - 8711500193605

8711500193612

EAN1

Bar code on outerbox - EAN3

Logistic code(s) - 928189305104

12NC

Net weight per piece 0.250 kg



Medium Pressure

Dimensional drawing







Product	C (Max)	D (Max)	O (Norm)
HOK 80/120	898.4	21.92	800



Medium Pressure

Photometric data







Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.