

PAR56 and PAR64



PAR64 1000W 240V MFL

PAR56 and PAR 64 – picking out the smallest of details. These self-contained spotlights are ideal for intensifying the visual experience in all kinds of clubs, that is because their accurate beam control picks out even the smallest of details even over long distances. This beam control makes the PAR 56 and PAR 64 excellent for long-range light projections. In addition, the universal burning feature provides complete flexibility of luminaires angle and position, while the front glass of the PAR56 provides thermal and physical protection. The result? Complete creative freedom to achieve the desired effect. Immediate re-strike also ensures instant resumption of entertainment after any power interruption.

Product data

• General Characteristics

ANSI Code	EXE
LIF Code	CP62
Cap-Base	GX16d
Bulb	PAR64 [PAR 64inch/180mm]
Burning Position	any
Main Application	Flood and Ambient Lighting
Gas Filling	GAS
Average Lifetime	300 hr
Life to 50% failures	300 (min) hr

• Electrical Characteristics

Rated Lamp Wattage	1000 W
Voltage	240 V
Dimmable	yes

• Light Technical Characteristics

Beam Description	Medium Flood
Beam Angle	23 D
Technical Beam Angle	23 D
Luminous Intensity	130000 (max) cd

Colour Temperature	3200 K
--------------------	--------


• Product Dimensions

Overall Length C	150 (max) mm
Diameter D	204 (max) mm

• Product Data

Order code	440761 10
Full product code	871150044076110
Full product name	PAR64 1000W 240V MFL
Order product name	PAR64 1000W 240V MFL
Pieces per pack	1
Packing configuration	6
Packs per outerbox	6
Bar code on pack - EAN1	8711500440761
Bar code on outerbox - EAN3	8711500440778
Logistic code(s) - 12NC	924783445504
Net weight per piece	760.000 gr

Dimensional drawing



PAR 64

Product	C (Max)	D (Max)
PAR64 1000W 240V MFL	150	204



© 2011 Koninklijke Philips Electronics N.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com/lighting

2011, May 4
data subject to change