

Halogen High Voltage DE

PF821 R 500W R7s 230V 1CT

The high, constant light output and consistent color temperature of these double ended high voltage halogen lamps ensure attractive, accurately exposed pictures for both film and video. In addition, the wide choice of dimensions and power ratings opens new levels of creative freedom for the luminaire designer.

Product data

• General Characteristics

Philips Code ANSI Code	PF821 R GDA
LIF Code	-
Cap-Base	R7s
Bulb Finish	Clear
Filament Shape	Coiled Coil
Operating Position	P4
Main Application	Video/Photo/Eng
Life to 50% failures	75 hr

• Electrical Characteristics

Lamp Wattage	500 W
Voltage	230 V
Dimmable	Yes
Rapid Acting HBC	4 V
Fuse	

• Light Technical Characteristics

Color Temperature	3200 K
Technical	
Luminous Flux Lamp	11000 Lm

Product Dimensions

Base	Face to	o Base	
Face	A		

128.2 (min), 129.8 (nom), 131.4 (max) mm

Overall Length C	133.2 (max) mm
Diameter D	11 (max) mm
Filament Length W	65 mm

Luminaire Design Requirements


Pinch Temperature	400 (max) C
Bulb Temperature	900 (max) C

• Product Data

Order code Full product code Full product name	923881743201 923881743201 PF821 R 500W R7s 230V 1CT
Order product name Pieces per pack	PF821 R 500W R7s 230V 1CT/10
Packing configuration	10
Packs per outerbox	10
Bar code on pack - EAN1	8711500492104
Bar code on outerbox - EAN3	8711500521897
Logistic code(s) - 12NC	923881743201
Net weight per piece	11.300 gr



Dimensional drawing



R7s, RX7s

Product	A (Min)	A (Norm)	A (Max)	C (Max)	D (Max)	W (Norm)
PF821 R 500VV R7s 230V	128.2	129.8	131.4	133.2	11	65





 $\textcircled{\sc c}$ 2011 Koninklijke Philips Electronics N.V. All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com/lighting