

# Halogen non-reflector

## 7787LL 400W G6.35 36V 1CT

Halogen non-reflector lamps offer high-quality light and are easy to install, replace and operate. All halogen non-reflector lamps incorporate a distortion-free quartz bulb and a precise positioning of the mounted filament. These ensure optimal beam performance and consistent, high light output. A wide range of wattages is available for a broad variety of applications, including projection systems. In addition you get all the proven advantages of halogen technology such as a full spectrum and a color rendering index (CRI) of 100 - the same as natural light and the best that it can be. Halogen lamps also create a comfortable warm white light, and they maintain their lumen output, with almost no reduction, throughout their lifetime.

#### Product data

#### • General Characteristics

Philips Code 7787LL ANSI Code LIF Code G6.35 Cap-Base

**Bulb Material** Quartz-UV Open

Filament Shape Operating Position Projection Main Application Life to 50% failures 300 hr

#### • Electrical Characteristics

Lamp Wattage 400 W Voltage 36 V

# • Light Technical Characteristics

Color Rendering

Index

100 Ra8 3350 K

Color Temperature

Technical

Luminous Flux Lamp 12200 Lm

# Product Dimensions

Overall Length C 60 (max) mm Diameter D 18 (max) mm

35.75 (min), 36 (nom), 36.25 (max) Light Center Length

Pin Diameter P Filament Dimensions (WxH) [mm]

0.95 (min), 1 (nom), 1.05 (max) mm

9.4x4.7

## · Luminaire Design Requirements

Pinch Temperature 350 (max) C **Bulb Temperature** 900 (max) C

#### • Product Data

924031523306 Order code 924031523306 Full product code

Full product name 7787LL 400W G6.35 36V 1CT 7787LL 400W G6.35 36V 1CT/3X8F Order product name

Pieces per pack 3X8F Packing configuration Packs per outerbox 24

8711500506559 Bar code on pack -

Bar code on inter-8711500420411

mediate packing -

EAN2

Bar code on 8711500422965

outerbox - EAN3

924031523306 Logistic code(s) -


12NC

Net weight per piece 8.333 gr



# Halogen non-reflector

# Dimensional drawing



# G6.35, GY6.35

Product	C (Norm)	C (Max)	D (Max)	L (Min)	L (Norm)	L (Max)	P (Min)	P (Norm)	P (Max)
7787LL 400W G6.35 36V	-	60	18	35.75	36	36.25	0.95	1	1.05







Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.