



TL-D Coloured

TL-D 36W Yellow SLV

Tubular low-pressure mercury vapour discharge lamps with a tube wall internally coated with a white fluorescent powder to convert the UV radiation produced by the mercury gas discharge into visible light

Product data

• General Characteristics

Cap-Base	G13
Bulb	T26
Main Application	-
Life to 50% failures	15000 hr
EM	

• Light Technical Characteristics

Color Code	16
Color Designation (text)	Yellow
Chromaticity Coordinate X	495 -
Chromaticity Coordinate Y	477 -
Luminous Flux Lamp EM	1580 Lm
Lumen Maintenance 2000h	85 %
Lumen Maintenance 5000h	75 %

• Electrical Characteristics

Lamp Wattage	36 W
Lamp Wattage Technical	36 W
Lamp Voltage	103 V
Lamp Current	0.440 A
Dimmable	Yes

• Environmental Characteristics

Energy Efficiency Label (EEL)	B
Mercury (Hg) Content	13.0 mg

• Product Dimensions

Base Face to Base Face A	1199.4 (max) mm
Insertion Length B	1204.1 (min), 1206.5 (max) mm
Overall Length C	1213.6 (max) mm
Diameter D	28 (max) mm


• Product Data

Order code	928048501605
Full product code	928048501605
Full product name	TL-D 36W Yellow SLV
Order product name	TL-D 36W Yellow SLV/25
Pieces per pack	1
Packing configuration	25
Packs per outerbox	25
Bar code on pack - EAN1	8711500727510
Bar code on outerbox - EAN3	8711500727527
Logistic code(s) - 12NC	928048501605
Net weight per piece	138.400 gr


PHILIPS

sense and simplicity



Dimensional drawing



Product	A (Max)	B (Min)	B (Max)	C (Max)	D (Max)
TL-D 36W/16	1199.4	1204.1	1206.5	1213.6	28



Photometric data



© 2011 Koninklijke Philips Electronics N.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com/lighting

2011, October 8
data subject to change